Pago Oprolsystemen

sales@aben.eu

www.haspel.expert

## Technische specificaties - Caractéristiques techniques - Technical specifications - Technische Daten



### RHK-1056

| | |
|---|---|
| Description | cable reel |
| Type of reel | Cable reel |
| Number of contacts | 3 |
| Conductor cross-section (mm²) | 0.75 |
| Length (m) | >0-5 |
| winding length cable max (m) | 3 |
| Max Volt (V) | 230 |
| Max Amp (A) | 10 |
| Cable mounted | yes |
| Cable Type | H03 VV-F |
| Drive | spring |
| Ratched Lock | yes |
| IP Class | IP40 |
| Material | plastic |
| Model | closed |
| Power (wound up)-(Watt) | 1000 |
| Power (unwound)-(Watt) | 2300 |
| Temperture (°C) | 5/35 |
| Application | economic |
| Thermic protection | no |
| overhang (m) | |
| Cable guide | no |
| Movement of reel | |
| Finishing | |
| Color | orange |
| Number of Cycle | 20000 |
| External cable diameter (mm) | |
| Height(mm) | 134 |
| Width(mm) | 135 |
| Depth(mm) | 94 |
| Kg | 0.8 |
| Cable end | free |
| Installation Position | |

RHK1056